

TC-80 TRACKED CONVEYOR



SPECIFICATION:

TC-80

Conveyor Length:	23.5m (77')
Belt Width:	1.05m (42")
Net Engine (Tier 3) Power:	36.4kW (49hp)
Max Discharge height:	10.5m (34'6") @ 28°

WORKS FOR YOU.

TC-80 TRACKED CONVEYOR



CONVEYOR


Conveyor Length	23.5m	77'
Belt Width	1050mm	42"
Conveyor Drive	Hydraulic	800cc
Discharge Height @ 24°	10.2m	33'6"
Max Discharge Height @ 28°	10.5m	34'6"
Capacity	Up to 400 TPH	
Hydraulic Folding Head Section		
Belt Type	Plain: 3 Ply	
Feedboot with removable 6mm steel wear liners		
Polyurethane tensioned belt cleaner		
Hydraulic feed in height adjustment		
Hydraulic fold over for Transport		
Hydraulic conveyor angle adjustment		
40 degree rollers		
Variable speed control		



Full Length Conveyor Skirting

POWERUNIT

Diesel Hydraulic	
Engine (Tier 3)	Deutz D2011 L04I - 36.4kW (49hp)
Fuel Tank Volume	200 litres
Hydraulic Oil Cooler	Standard



Feed Boot Liner Extension and Dust Covers



Deutz D2011 36.4kW(49hp) Engine

CHASSIS

Tracks	2.9m centres x 400mm shoe
2 Speed Track Motor	
Lower Speed	0.9Km/h
Higher Speed	1.6Km/h

GENERAL

Heavy duty undercarriage unit with 400mm wide tracks
External conveyor belt adjustment
Engine prestart delay & siren
Low level greasing
Emergency stops (4 nr)
Machine Painted, Black-RAL9005 & Grey-RAL7024
Safety guards in compliance with machinery directive



Transport mode



Working mode

OPTIONS EQUIPMENT

Deutz TD 2.9 L04 45kW (60hp) Tier 4 Final Engine
6mm AR400 Steel Wear Feedboot Liners
20mm Rubber Wear Feedboot Liners
Feedboot Extension c/w Steelwear Liners
Feedboot Extension c/w 20mm rubber Wear Liners
Feedboot Extension c/w 6mm AR400 Steelwear Liners
Impact Rollers at Feedboot area
Blade type / Primary scraper
Conveyor fitted with Chevron belt 3 ply x 4+2 covers
Conveyor fitted with Heavy duty plain belt 3 ply x 5+2 covers
Conveyor Under Guarding up To 2.5 Meters @12degree incline
Conveyor Head drum Guarding
Conveyor Dust covers
Conveyor Water Dust Suppression (Spray bar only)
Conveyor Full length skirting
Powerunit c/w Hydraulic oil, Century 100 - (Recommended for ambient temperatures between +15 to +50°C)
Radio remote control system for crawler tracks
Pull cord emergency stop
Special paint colour (if different from above). RAL must be specified on order

TRANSPORT DIMENSIONS



MACHINE WEIGHT: 13,100kg (28880lbs)



Follow us on:



www.terexfinlay.com

Effective January 2016. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and Terex GB Ltd. makes no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade-names of Terex Corporation and/or its subsidiaries in the USA and other countries. All rights are reserved. Terex® is a registered trademark of Terex Corporation in the USA and many other countries. Copyright 2010 Terex GB Ltd.



TEREX® | FINLAY

WORKS FOR YOU.™