



TRACKED MOBILE CONE CRUSHER



C-1540RS



WORKS FOR YOU.™

C-1540RS

The Terex Finlay C-1540RS tracked mobile cone crusher provides the versatility of a crushing and screening plant on one machine in aggregate and ore surface mining applications. Based on the proven and tested Terex Finlay C-1540 cone crusher, this machine variant features an innovative on-board recirculating system and detachable sizing screen. If recirculation and sizing of materials is not required the sizing screen can be quickly detached from the machine without the need for lifting equipment.

The Terex Finlay C-1540RS can be fitted with an optional patented pre-screen module which allows fines materials to be removed prior to being fed to the crushing chamber offering higher production with lowest cost per ton wear and running costs. The large hopper/feeder has an automated metal detection and a purge system to protect the cone and reduce downtime by removing metal contaminants from the feed belt.

STANDARD FEATURES

Engine:

Tier 3 / Stage IIIA: Caterpillar C13 ACERT 328kW (440hp)
Tier 4i / Stage IIIB: Scania DC13 331kW (450hp)
Tier 4 F / Stage IV: Scania DC13 331kW (450 hp)

Cone:

Terex 1000 Cone chamber, Head diameter: 1000mm (40")
Long throw eccentric, medium coarse concave (max feed size 160mm)
Hydrostatic cone drive

Hopper / Feeder:

Hopper capacity: 5m³ (6.5yd³)
Belt width: 1.05m (42")
Metal detector
Metal contaminants purge system
Wear resistant liner plates

Main Conveyor:

Belt width: 900mm (36")
High spec scraper at head drum
Wear resistant liners at crusher discharge point
Dust Covers

Re-Circulating System:

Two deck screen: 3.66m x 1.53m (12' x 5')
Top deck mesh fitted to screen - 40mm aperture fitted unless specified otherwise
Oversize transfer conveyor, re-circulating conveyor and fines conveyor fitted as standard
Quick detach screen and fines conveyor
Note:- Middle grade transfer conveyor is not fitted, this is only an option

General:

Galvanised catwalk c/w handrail, kick board and access ladders
Heavy duty track unit, sprocket centres 3.8m, pad width 500mm
Hand held track control set with connection lead
Standard oils - (Recommended for ambient temperatures between -5 to +30°C)
Safety guards in compliance to machinery directive
One auxiliary drive
Emergency stops
Piped for dust suppression c/w spraybars
High specification oil cooler

Hopper / Feeder

- ▶ Hopper capacity: 5m³ (6.5yd³)
- ▶ Hopper fabricated in 10mm mild steel plate with 10mm wear resistant steel liners at input point
- ▶ Hopper Width at rear: 2.45m (8')
- ▶ Hopper Width at rear with optional hopper extensions: 3.7m (12' 2")
- ▶ Belt Spec: Plain
- ▶ Belt Width: 1.05m (42")
- ▶ Speed range: variable, 0 – 31 m/min (0 – 101 ft/min)
- ▶ Working Angle: 24° (Pre-screen feed), 21° (Direct feed)
- ▶ Drop down rear door for auxiliary crusher feed
- ▶ Crash bar fitted to reduce impact load on feed conveyor

Powerpack

- ▶ Tier 3 / Stage IIIA : Caterpillar C13 ACERT
Engine Power: 328kW (440hp)
Engine Speed: 1900 rpm
- ▶ Tier 4i / Stage IIIB : Scania DC13
Engine Power: 331kW (450hp)
Engine Speed: 1900 rpm
- ▶ Tier 4F / Stage IV : Scania DC13
Engine Power: 331kW (450hp)
Engine Speed: 1900 rpm

Fines Conveyor

- ▶ Belt width: 1.4m (55")
- ▶ Belt spec: Plain
- ▶ Working Angle: 19° - 22°
- ▶ Speed: 70 – 80 m/min (229 – 262 ft/min)
- ▶ Hydraulically folds for transport
- ▶ Discharge Height: 3.0m (9' 10")
- ▶ Stockpile capacity: 44.3m³ (58yd³) @ 40°

Screen box

- ▶ Top deck: 3.66m x 1.53m (12' x 5')
- ▶ Bottom deck: 3.05m x 1.53m (10' x 5')
- ▶ Total screening area: 10.1m² (110ft²)
- ▶ Screen Angle: 19° - 22°

Oversize Transfer Conveyor

- ▶ Belt width: 500mm (20")
- ▶ Belt spec: Plain
- ▶ Speed: Variable speed, 0 - 90 m/min (0 - 295 ft/min)
- ▶ Hydraulically folds for transport

Recirculation conveyor

- ▶ Belt width: 500mm (20")
- ▶ Belt spec: Chevron
- ▶ Working Angle: 30°
- ▶ Speed: Variable speed, 0 - 90 m/min (0 - 295 ft/min)
- ▶ Hydraulically folds for transport

Undercarriage

- ▶ Shoe Width: 500mm (20")
- ▶ Sprocket Centres: 3.80m (12' 6")
- ▶ Tracking Speed: 0.9 km/h
- ▶ Gradeability: 25°

Cone chamber

- ▶ Terex 1000mm (40") cone chamber
- ▶ Cone Counter Shaft Speed Range: 840 - 940 rpm
- ▶ Variable speed control settings for producing a quality aggregate
- ▶ 'On the fly' hydraulically adjustable closed side setting with monitoring system

Features:

- ▶ Detachable 3.66m x 1.53m (12' x 5') double deck sizing screen passes oversize material back to the crusher via the on-board recirculating conveyor.
- ▶ Quick and easy detachable screen and fines conveyor for open circuit crushing.
- ▶ The optional stacking conveyor in conjunction with the optional lower deck screen, produces a 2nd spec'd product.



Transport Dimensions



Working Dimensions



Machine Weight: * 46,180kg (101,810lbs) Without options
* 49,060kg (108,159lbs) * With optional pre-screen
* 50,760kg (111,907lbs) * With optional pre-screen, mid-grade transfer & mid-grade stockpiling conveyor

Follow us on:



www.terexfinlay.com

Effective January 2015. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and Terex GB Ltd. makes no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade-names of Terex Corporation and/or its subsidiaries in the USA and other countries. All rights are reserved. Terex® is a registered trademark of Terex Corporation in the USA and many other countries. Copyright 2010 Terex GB Ltd.



TEREX® | FINLAY

WORKS FOR YOU.™